

MULTI-ROOM AUDIO

MM4100B

4 ZONE AMPLIFIER

NETWORK MULTI-ROOM AUDIO

Exceptional audio performance for premium whole-house sound.

**DESIGNED FOR HIGH-END MULTI-ROOM AUDIO**

A stable Class D platform distributes powerful, low-distortion audio across four zones, with independent inputs and gain controls, bridgeable outputs, Apple AirPlay 2 and integrated online music services.

4

AUDIO ZONES

8 x 50 W

CHANNEL OUTPUT

105 dB

SIGNAL-TO-NOISE

5 Hz - 72 kHz

FREQUENCY RESPONSE

Power and flexibility, by zone.

Engineered for custom multi-room distribution in premium residential audio systems.

- **STABLE CLASS D DESIGN**

Audiophile sound quality with efficient operation.

- **INDEPENDENT + BUS INPUTS**

Flexible routing for custom multi-zone systems.

- **BRIDGEABLE OUTPUTS**

Additional output power when the application requires it.

- **APPLE AIRPLAY 2**

Integrated support for convenient network audio playback.

- **MULTI-STAGE PROTECTION**

Protection circuitry and temperature-controlled cooling.



TECHNICAL SPECIFICATIONS

WEIGHT

9 kg (19.48 lb)

DIMENSIONS

42.4 x 36.2 cm (16.7 x 14.25 in)

OUTPUT CHANNELS

8

POWER OUTPUT

50 W/ch RMS @ 8 ohm

BRIDGED OUTPUT

100 W/ch RMS @ 8 ohm

AUTO-ON SENSITIVITY

13.7 mV

FREQUENCY RESPONSE

5 Hz - 72 kHz

SIGNAL-TO-NOISE RATIO

105 dB A-weighted

THD @ 50 W

.005% (20 Hz - 20 kHz)

THD BRIDGED @ 100 W

.010% (20 Hz - 20 kHz)

VOLTAGE REQUIREMENT

115/230 VAC, 60/50 Hz

STANDBY POWER

0.264 W @ 115 V