

MULTI-ROOM AUDIO

MM4200C

4 ZONE AMPLIFIER

NETWORK MULTI-ROOM AUDIO

High-output amplification for premium whole-house audio.

**DESIGNED FOR HIGH-END MULTI-ROOM AUDIO**

A stable Class D platform delivers powerful, low-distortion audio across four zones, with independent and bus inputs, bridgeable outputs, per-channel gain control, Apple AirPlay 2 and online music services.

4

AUDIO ZONES

8 x 100 W

CHANNEL OUTPUT

105 dB

SIGNAL-TO-NOISE

5 Hz - 72 kHz

FREQUENCY RESPONSE

Power and flexibility, by zone.

Engineered for high-output custom multi-room distribution in premium residential systems.

- **STABLE CLASS D DESIGN**

Superior audiophile sound quality with efficient operation.

- **HIGH-OUTPUT CHANNELS**

Eight channels rated at 100 watts per channel RMS.

- **INDEPENDENT + BUS INPUTS**

Flexible routing for custom multi-zone systems.

- **BRIDGEABLE OUTPUTS**

Up to 200 watts per bridged channel when required.

- **APPLE AIRPLAY 2**

Integrated network playback and online music-service support.



TECHNICAL SPECIFICATIONS

WEIGHT

9 kg (19.48 lb)

DIMENSIONS

42.4 x 36.2 cm (16.7 x 14.25 in)

OUTPUT CHANNELS

8

POWER OUTPUT

100 W/ch RMS @ 8 ohm

BRIDGED OUTPUT

200 W/ch RMS @ 8 ohm

AUTO-ON SENSITIVITY

13.7 mV

FREQUENCY RESPONSE

5 Hz - 72 kHz

SIGNAL-TO-NOISE RATIO

105 dB A-weighted

THD @ 100 W

.005% (20 Hz - 20 kHz)

THD BRIDGED @ 200 W

.010% (20 Hz - 20 kHz)

VOLTAGE REQUIREMENT

115/230 VAC, 60/50 Hz

STANDBY POWER

0.264 W @ 115 V